



TECHNICAL DATA SHEET

ENDUROX HD 30

Heavy-Duty Engine Oil

DESCRIPTION:

Endurox HD 30 is developed for diesel and gasoline heavy-duty engines, operating under moderate to severe conditions. Endurox HD is also suitable for stationary engines. The oil is in particular suitable for use in Diesel engines which are operated on low sulphur fuels but also on, still widely available, fuels containing sulphur at elevated levels up to 1.5%

Endurox HD is also available in SAE 10W/40/50/25W-60.



BENEFITS:

- High dispersancy and detergency properties
- Good anti-wear, anti-foam and anti-corrosion properties
- Excellent thermal and oxidation stability

PERFORMANCE LEVELS:

- API CF/SG
- CAT TO-2
- CCMC G2/D2
- MIL-L-2104D
- MIL-L-46152D
- MTU Type 2

TYPICAL PROPERTIES

SAE	Unit	30
Density 15 °C:	Kg/m ³	883
Viscosity 40 °C	cSt	94
Viscosity 100 °C	cSt	10.8
Viscosity Index		98
Pour Point	°C	-30
Flash Point	°C	230
Total Base Number (TBN)	mg KOH/g	12.6



RYMAX LUBRICANTS B.V. Delweg 8
The Netherlands 6902 PJ Zevenaar

T +31 (0) 316 740 856

E info@rymax-lubricants.com

W www.rymax-lubricants.com

[WWW.FACEBOOK.COM/RYMAXLUBRICANTS](https://www.facebook.com/RYMAXLUBRICANTS)

[WWW.INSTAGRAM.COM/RYMAXLUBRICANTS](https://www.instagram.com/RYMAXLUBRICANTS)

All performance data on this Technical Data Sheet are indicative only and can vary during production

LUB002005

Version Number: 3

Date:
01-07-2023