



TECHNICAL DATA SHEET

ENDUROX HD 40

Heavy-Duty Engine Oil

DESCRIPTION:

Endurox HD 40 is developed for diesel and gasoline heavy-duty engines, operating under moderate to severe conditions. Endurox HD is also suitable for stationary engines. The oil is in particular suitable for use in Diesel engines which are operated on low sulphur fuels but also on, still widely available, fuels containing sulphur at elevated levels up to 1.5%

Endurox HD is also available in SAE 10W/30/50/25W-60.



BENEFITS:

- High dispersancy and detergency properties
- Good anti-wear, anti-foam and anti-corrosion properties
- Excellent thermal and oxidation stability

PERFORMANCE LEVELS:

- API CF/SG
- CAT TO-2
- CCMC G2/D2
- MIL-L-2104D
- MIL-L-46152D
- MTU Type 2

TYPICAL PROPERTIES

SAE	Unit	40
Density 15 °C:	Kg/m ³	892
Viscosity 40 °C	cSt	146
Viscosity 100 °C	cSt	13.5
Viscosity Index		85
Pour Point	°C	-30
Flash Point	°C	240
Total Base Number (TBN)	mg KOH/g	12.8



RYMAX LUBRICANTS B.V. Delweg 8
The Netherlands 6902 PJ Zevenaar

T +31 (0) 316 740 856 **E** info@rymax-lubricants.com
W www.rymax-lubricants.com

F WWW.FACEBOOK.COM/RVMAXLUBRICANTS
I WWW.INSTAGRAM.COM/RVMAXLUBRICANTS

All performance data on this Technical Data Sheet are indicative only and can vary during production LUB002006 Version Number: 3

Date:
01-07-2023