TECHNICAL DATA SHEET

ENDUROX SD 15W-40

Heavy-Duty Engine Oil

DESCRIPTION:

Endurox SD 15W-40 is our reliable engine oil, developed for diesel and petrol engines in commercial vehicles. It is developed according to exhaust emission norms for Euro III, Euro II and Euro I engines. It meets all API CH-4 requirements for heavy-duty engine lubricants, next to a wide range of OEM specifications. It offers excellent all-round performance for mixed fleets, including naturally aspirated and turbocharged engines operating under moderate to heavy working conditions. Its balanced formulation provides effective protection against engine wear while helping to control sludge and deposits. Rymax Endurox SD oils are not suitable for engines equipped with DPF filters.



BENEFITS:

- Excellent thermal and oxidation stability
- High dispersancy and detergency properties, ensuring a clean engine operation
- Excellent anti-wear, anti-corrosion and anti-foam properties
- Stable viscosity for reliable lubrication under varying operating conditions

PERFORMANCE LEVELS:

- API CH-4/SJ
- ACEA E7
- CAT ECF-1A
- Cummins CES 20077
- Cummins CES 20076
- Deutz DQC III-10
- MB 228.1
- MTU type 2
- Volvo VDS-2

TYPICAL PROPERTIES

SAE	Unit	15W-40
Density 15 °C	Kg/m3	879
Viscosity 40 °C	cSt	102
Viscosity 100 °C	cSt	14.30
Viscosity Index		140
Pour Point	°C	-33
Flash Point	°C	220
Total Base Number (TBN)	mg KOH/g	11

RYMAX B.V.
The Netherlands
Delweg 8
6902 PJ Zevenaar
T +31 (0) 316 740 856
F +31 (0) 316 740 844
E info@rymax-lubricants.com
W www.rymax-lubricants.com
WWW.FACEBOOK.COM/RYMAXLUBRICANTS
WWW.INSTAGRAM.COM/RYMAXLUBRICANTS

All performance data on this Technical Data Sheet are indicative only and can vary during production

LUB002315 Version Number: 1

Date:
26-10-2026