


## **TECHNICAL DATA SHEET**

# **ENDUROX XLD 10W-40**

Full Synthetic Heavy-Duty Engine Oil

#### **DESCRIPTION:**

Endurox XLD 10W-40 is our full synthetic Ultra High Performance diesel engine oil for heavy-duty engines, developed to meet the requirements of most modern European engines meeting Euro II, III, IV and V emission norms. It is formulated with premium quality synthetic base oils and advanced additive packages to offer superior engine protection and significantly extend drain intervals. This oil meets the latest ACEA E7 & ACEA E4 specifications and is suitable for severe heavy-duty applications and extended service life in most modern European vehicles.





#### **BENEFITS:**

- Extended drain intervals due to superior TBN retention
- · Excellent soot handling capability minimizes soot related wear
- Excellent thermal and oxidation stability
- Excellent protection from rust, foam and corrosion
- Excellent low temperature properties to ensure easy cold start

#### **PERFORMANCE LEVELS:**

- API CI-4
- ACEA E4
- ACEA E7
- Cummins CES 20077
- Cummins CES 20078
- Deutz DQC III-10
- Mack EO-N
- MAN M3277
- MB 228.5
- MTU Type 3
- Renault RXD/RLD-2
- Scania LDF-2
- Volvo VDS-3

### **TYPICAL PROPERTIES**

| SAE                     | Unit     | 10W-40 |
|-------------------------|----------|--------|
| Density 15 °C:          | Kg/m3    | 863    |
| Viscosity 40 °C         | cSt      | 98.2   |
| Viscosity 100 °C        | cSt      | 14.9   |
| Viscosity Index         |          | 159    |
| Pour Point              | °C       | -36    |
| Flash Point             | °C       | 240    |
| Total Base Number (TBN) | mg KOH/g | 12.8   |



RYMAX LUBRICANTS B.V. Delweg 8

Delweg B 6902 PJ Zevenaar T +31 (0) 316 740 856

E info@rymax-lubricants.com W www.rymax-lubricants.com

